
BRIDGE REPAIR AND INSPECTION VEHICLE



LIFT-A-LOFT

An Industry Leader for 55 Years

TMX Series

The TMX Series provides a maneuverable alternative for bridge repair and inspections. The telescopic scissors assembly minimizes wheelbase requirements; this provides maximum maneuverability without compromising platform height.

DIMENSIONS:

MAX. PLATFORM HEIGHT: _ _ _ 32' (9.75m)
MIN. PLATFORM HEIGHT: _ _ _ .6'3" (1.90m)
TRAVEL HEIGHT: _ _ _ _ _ 9'6" (2.90m)
GUARD RAIL HEIGHT: _ _ _ _ 39" (0.99m)
PLATFORM SIZE: _ _ _ _ _ 84" X 216"
(2.13 X 5.49m)
PLATFORM CAPACITY: -4,000 lbs. (1814.4 kg)

PLATFORM CONTROLS:

Include pedestal with stabilizer raise/lower and ignition switch with anti re-start. A moveable pendant controller includes control switches for raising and lowering the unit.

AVAILABLE OPTIONS:

- 2' (0.61m) Side Deck Slider Panels
- Cold Weather Package
- Platform Mounted Flood Lights
- Hydraulic Driven Air Compressor
- 12VDC To 110VAC Power Inverter
- Flashing Safety Lights on Platform
- Flashing Safety Lights on Rear Bumper
- Flashing Safety Lights on Stabilizers
- Tail Lift
- Alternate Platform Sizes Available
- Different Makes and Models of Chassis
- Other Custom Options May be Available to fit your specific requirement



TRUCK REQUIREMENTS:

GVW: _ _ _ _ _ 30,000 lbs. (13,608 kg) Minimum
WHEELBASE: _ _ _ _ _ 170" (4.32m) Minimum
IDLE SHUT DOWN: _ _ _ _ Should Not be Included

SAFETY FEATURES:

- Emergency Stop Push Buttons
- Emergency Operation Controls
- Holding Valves on Lift Cylinders
- Lanyard Attachment Points
- Non-Skid Platform
- Scissor Spreader for Maintenance & Inspection
- Flashing Lights
- Hydraulic Powered Stabilizers
- Lowering Alarm
- Starter Interlock Prevents Attempted Restarts of Running Engine
- Transmission Neutral/ Emergency Brake Interlocks
- Platform / Stabilizer Safety Interlocks
- Indicator Lights in Cab and at Base Control Station
- Emergency Back up Controls at Base.

LIFT-A-LOFT